



COMPONENT	SPECIFICATION
POLE SHAFT	ASTM A500 GR.B
MISC. STEEL	ASTM A36
ANCHOR BOLTS	ASTM F1554 GR. 55
BASE PLATE	ASTM A36

GENERAL NOTES:

- ALL HARDWARE TO BE GALVANIZED TO ASTM A153.
- POLE ASSEMBLY TO BE GALVANIZED TO ASTM A123.
- ALL WELDING TO CONFORM TO AWS D1.1 MOST RECENT EDITION.
- DESIGN INCORPORATE GUST FACTOR PER REF CODE.
- REFER TO GENERAL INSTALLATION INSTRUCTIONS PRIOR TO ASSEMBLY.

FINISH: WIND SPEED: DESIGN CRITERIA:

GALVANIZED 80 MPH 110 MPH AASHTO LTS 3 ASCE

PAINTED 90 MPH 120 MPH AASHTO LTS 6 DSA

PAINTED & GALV 100 MPH ___ MPH IBC UBC

LOADING DATA			
90 MPH	100 MPH	110 MPH	120 MPH
13 EPA	9 EPA	8 EPA	6 EPA
325 LBS	225 LBS	200 LBS	150 LBS

DETAIL 2 MATERIAL SPECIFICATIONS

MSM
Makers Sales and Marketing, LLC

2316 WEAVER ST.
HALTOM CITY, TX 76117
METRO (817) 834-5538
TOLL FREE (866) 724-4527
FAX (817) 831-6088

DATE:	REV.:	JOB NO.:	SCALE:
	00	N/A	NTS
DRAWING NUMBER:		DRAWN BY:	QUOTE NUMBER:
MRT2559AB		DR	N/A